


Extended Surface Metal Frame Pre-Filter | Panel Filter



Technical Data		
Filter Media	Synthetic Fibre	
Frame Material	Galvanized Steel	
Average Gravimetric Efficiency	80-90 %	>90 %
Classification (EN 779:2002)	G3	G4
Eurovent Class	EU3	EU4
Initial Pressure Drop	75	85
Final Pressure Drop	450 Pa	450 Pa
Max. Temperature	100 °C	100 °C
Max. Moisture	100 %	100 %

Extended Surface Cardboard Frame Pre-Filter | Panel Filter



Technical Data		
Filter Media	Synthetic Fibre	
Frame Material	Cardboard	
Average Gravimetric Efficiency	>90 %	
Classification (EN 779:2002)	G4	
Eurovent Class	EU4	
Initial Pressure Drop	70	
Final Pressure Drop	250 Pa	
Max. Temperature	100 °C	
Max. Moisture	100 %	

Product Code	Dimensions (WxHxD)	Media Area (m ²)	Air Flow (m ³ /h)	Press. Drop (Pa)	Weight (Kg)
G3 (EU3) - G4 (EU4)					
C-KSGZ/287/287/48-G4	287x287x48	0,15	850	60	1,45
C-KSGZ/400/500/48-G4	400x500x48	0,34	1950	60	0,70
C-KSGZ/500/500/48-G4	500x500x48	0,42	2450	60	0,80
C-KSGZ/500/625/48-G4	500x625x48	0,53	3000	60	0,90
C-KSGZ/287/592/48-G4	287x592x48	0,3	1700	60	0,70
C-KSGZ/490/592/48-G4	490x592x48	0,49	2820	60	0,85
C-KSGZ/592/592/48-G4	592x592x48	0,6	3400	60	1,00
C-KSGZ/287/287/98-G4	287x287x98	0,2	1000	70	1,8
C-KSGZ/400/500/98-G4	400x500x98	0,48	2400	70	0,88
C-KSGZ/500/500/98-G4	500x500x98	0,6	3000	70	1,1
C-KSGZ/500/625/98-G4	500x625x98	0,75	3600	70	1,2
C-KSGZ/287/592/98-G4	287x592x98	0,4	2100	70	0,9
C-KSGZ/490/592/98-G4	490x592x98	0,7	3500	70	1,1
C-KSGZ/592/592/98-G4	592x592x98	0,85	4250	70	1,35