

Extended Surface Metal Frame Washable Pre



Technical Data

Filter Media	Polyurethane Foam	
Frame Material	Galvanized Steel	
Average Gravimetric Efficiency	65-80 %	80-90 %
Classification (EN 779:2002)	G2	G3
Eurovent Class	EU3	EU3
Initial Pressure Drop	10-25	30
Final Pressure Drop	450 Pa	450 Pa
Max. Temperature	100 °C	100 °C
Max. Moisture	100 %	100 %

Product Code	Dimensions (WxHxD)	Media Area (m ²)	Air Flow (m ³ /h)	Press. Drop (Pa)	Weight (Kg)
POL 20/10 - POL 45/10					
C-KPGZ/287/287/48-G2-G3	287x287x48	0,25	850	25	2
C-KPGZ/400/500/48-G2-G3	400x500x48	0,6	1950	25	3,4
C-KPGZ/500/500/48-G2-G3	500x500x48	0,8	2450	25	3,9
C-KPGZ/500/625/48-G2-G3	500x625x48	1	3000	25	4
C-KPGZ/287/592/48-G2-G3	287x592x48	0,5	1700	25	3,2
C-KPGZ/490/592/48-G2-G3	490x592x48	0,9	2820	25	3,9
C-KPGZ/592/592/48-G2-G3	592x592x48	1,1	3400	25	4,5

Straight Surface Metal Frame Pre-filter | Panel Filter



Technical Data

Filter Media	Synthetic Fibre	
Frame Material	Galvanized Steel	
Average Gravimetric Efficiency	65-80 %	80-90 %
Classification (EN 779:2002)	G2	G3
Eurovent Class	EU2	EU3
Initial Pressure Drop	20-35	40
Final Pressure Drop	250 Pa	250 Pa
Max. Temperature	100 °C	100 °C
Max. Moisture	100 %	100 %

Product Code	Dimensions (WxHxD)	Media Area (m ²)	Air Flow (m ³ /h)	Press. Drop (Pa)	Weight (Kg)
POL					
C-KPGD/202/400/10-G2	202x400x10	0,08	785	20	0,3
C-KPGD/202/500/10-G2	202x500x10	0,10	980	20	0,3
C-KPGD/202/700/10-G2	202x700x10	0,14	1375	20	0,35
C-KPGD/202/900/10-G2	202x900x10	0,18	1760	20	0,38
SNC					
C-KSGD/202/400/10-G2	202x400x10	0,08	785	40	0,3
C-KSGD/202/500/10-G2	202x500x10	0,10	980	40	0,3
C-KSGD/202/700/10-G2	202x700x10	0,14	1375	40	0,35
C-KSGD/202/900/10-G2	202x900x10	0,18	1760	40	0,38