

Metal Frame Coarse Dust Pocket Filter | Bag Filter



Technical Data

Filter Media	Synthetic Fibre	
Frame Material	Galvanized Steel	
Average Gravimetric Efficiency	80-90 %	90 %
Classification (EN 779:2002)	G3	G4
Eurovent Class	EU3	EU4
Initial Pressure Drop	35	40
Final Pressure Drop	250 Pa	250 Pa
Max. Temperature	100 °C	100 °C
Max. Moisture	100 %	100 %

Metal Frame Fine Dust Pocket Filter | Bag Filter



Technical Data

Filter Media	Synthetic Fibre	
Frame Material	Galvanized Steel	
Average Gravimetric Efficiency	40-60 %	60-80 %
Classification (EN 779:2002)	F5	F6
Eurovent Class	EU5	EU6
Initial Pressure Drop	60	80
Final Pressure Drop	450 Pa	
Max. Temperature	80 °C	
Max. Moisture	100 %	

Product Code	Dimensions (WxHxD)	Bags	Media Area (m ²)	Air Flow (m ³ /h)	Press. Drop (Pa)	Weight (Kg)
G3-G4						
C-TF/GS3-287/592/360-G3-G4	287x592x360	3	1,3	1700	45	1,1
C-TF/GS5-490/592/360-G3-G4	490x592x360	5	2,2	2800	45	1,7
C-TF/GS6-592/592/360-G3-G4	592x592x360	6	2,6	3400	45	2
F5						
C-TF/287/592/380-F5	287x592x380	3	1,5	1125	40	1,3
C-TF/287/592/380-F5	490x592x380	5	2,4	2100	40	1,8
C-TF/287/592/380-F5	592x592x380	6	2,9	2250	40	2,1
C-TF/287/592/500-F5	287x592x600	3	2,3	1700	50	2,4
C-TF/287/592/500-F5	490x592x600	5	3,9	2800	50	2
C-TF/287/592/500-F5	592x592x600	6	4,8	3400	50	1,4
F6						
C-TF/287/592/535-F6	287x592x535	4	2,8	1125	50	1,2
C-TF/490/592/535-F6	490x592x535	6	4,4	1870	50	1,8
C-TF/592/592/535-F6	592x592x535	8	5,8	2250	50	2,4
C-TF/287/592/635-F6	287x592x635	4	3,4	1700	65	1,3
C-TF/490/592/635-F6	490x592x635	6	5,1	2800	65	1,9
C-TF/592/592/635-F6	592x592x635	8	7,2	3400	65	2,6