

Metal Frame Fine Dust Pocket Filter | Bag Filter



Technical Data

Filter Media	Synthetic Fibre
Frame Material	Galvanized Steel
Average Gravimetric Efficiency	80-90 %
Classification (EN 779:2002)	F7
Eurovent Class	EU7
Initial Pressure Drop	125
Final Pressure Drop	450 Pa
Max. Temperature	80 °C
Max. Moisture	100 %

Metal Frame Fine Dust Pocket Filter | Bag Filter



Technical Data

Filter Media	Synthetic Fibre
Frame Material	Galvanized Steel
Average Gravimetric Efficiency	90-95 % >95 %
Classification (EN 779:2002)	F8 F8
Eurovent Class	EU8 EU8
Initial Pressure Drop	125 135
Final Pressure Drop	450 Pa
Max. Temperature	80 °C
Max. Moisture	100 %

Product Code	Dimensions (WxHxD)	Bags	Media Area (m ²)	Air Flow (m ³ /h)	Press. Drop (Pa)	Weight (Kg)
▼ F7						
C-TF/287/592/535-F7	287x592x535	4	2,9	1125	70	1,2
C-TF/490/592/535-F7	490x592x535	6	4,4	1870	70	1,8
C-TF/592/592/535-F7	592x592x535	8	5,8	2250	70	2,4
C-TF/287/592/635-F7	287x592x635	4	3,4	1700	85	1,3
C-TF/490/592/635-F7	490x592x635	6	5,1	2800	85	1,9
C-TF/592/592/635-F7	592x592x635	8	7,2	3400	85	2,6
▼ F8-F9						
C-TF/287/592/535-F8-F9	287x592x535	4	2,9	1125	85	1,2
C-TF/490/592/535-F8-F9	490x592x535	6	4,4	1870	85	1,8
C-TF/592/592/535-F8-F9	592x592x535	8	5,8	2250	85	2,4
C-TF/287/592/635-F8-F9	287x592x635	4	3,4	1700	95	1,3
C-TF/490/592/635-F8-F9	490x592x635	6	5,1	2800	95	1,9
C-TF/592/592/635-F8-F9	592x592x635	8	7,2	3400	95	2,6